







Air Purification & Effective Removal

High Pressure Pump specifications

Premium Series Electric Data and Specifications							
Pump Model 60 Hz	Size GPM	Motor HP	Unit RPM	Volts / Phase	Full Load Amps	Dimensions Inches	Weight lbs
96100	1	1	490	110-1	12.6	26 x 16 x 12	110
96100.SOL	1	1	490	110-1	12.6	26 x 16 x 12	110
96120	1	1	490	220-1	6.3	26 x 16 x 12	110
96120.SOL	1	1	490	220-1	6.3	26 x 16 x 12	110
96200	2	1.5	930	110-1	15	26 x 16 x 12	118
96200.SOL	2	1.5	930	110-1	15	26 x 16 x 12	118
96220	2	1.5	930	220-1	7.5	26 x 16 x 12	118
96220.SOL	2	1.5	930	220-1	7.5	26 x 16 x 12	118
96300	3	3	630	220-1	13.5	26 x 16 x 12	130
96300.SOL	3	3	630	220-1	13.5	26 x 16 x 12	130

Nozzle specifications

STANDARD NOZZLE SPECIFICATIONS					
Part Number	Orifice Diameter	GPM/LPM at 1000PSI	Description	O-Ring Color	
93508	.008"/.2mm	.020/.076	Brass & Stainless Steel Nozzle	red	
93512	.012"/.3mm	.029/.110	Brass & Stainless Steel Nozzle	black	
80450	.016"/.4mm	.044/.167	Brass & Stainless Steel Nozzle	brown	
93520	.020"/.5mm	.055/.208	Brass & Stainless Steel Nozzle	green	

Tubing specifications

HIGH PRESSURE NYLON TUBING				
Part No.	Length	Size	Psi Rating	Description
93072	500 ft	.375" OD/ .225" ID	1000//70bar	black nylon coil
90063	100 ft	.375" OD/ .225" ID	1000/70bar	black nylon coil
92700	50 ft	.375" OD/ .225" ID	1000/70bar	black nylon coil
92713	30"	.375" OD/ .225" ID	1000/70bar	black nylon straight length
92990	24"	.375" OD/ .225" ID	1000/70bar	black nylon straight length



**Air Purification &
Effective Removal**

Filtration specifications

FILTRATION				
Part Number	Description	Capacity GPM/LPM	Dimensions	Weight lbs
10109	In-line calcium inhibitor filter	0.5/2.0	2"dia. x 6.5"	.54
92608	9¾ filter cartridge 5 micron	5/19	2.75"dia. x 10"	.38
92603	9¾ filter cartridge 1 micron	5/19	2.75"dia. x 10"	.38
92526	9¾ pleated washable 10 micron cartridge	5/19	2.75"dia. x 10"	.38
93039	9¾ Phosphate cartridge	3/12	3"dia. x 9.625"	2.4
92609	10" filter housing with 1/2" ports	5/19	4.5"dia. x 12"	2.0
92611	10" dual filter housing with 1" ports	30/114	7.5"dia. x 13"	4.5
92612	10" dual filter cartridge 25/1 micron	15/57	4.5"dia. x 10"	1.0
95022	Mounting bracket for 92609			
95024	Replacement O-ring for 92609			